

BAVARIAN POLYMERS

6000 BRICKMOLD DP50 WINDOW



WHITE, TAN OR CLAY – LAMINATES available in either wood grains or color

SPECIFICATIONS

FRAME

- .065" TYPICAL WALL THICKNESS
- 3.200" OVERALL FRAME DEPTH
- 5/8" x 3/4" INTEGRAL J-CHANNEL
- 2-3/4" JAMB REVEAL
- 1-1/4" LONG NAILING FIN; 1-1/4" SET-BACK
- 1.280" x .590" BALANCE SHOE POCKET
- 7/8" OVERALL INSULATING GLASS CAPABILITY
- WELDED CONSTRUCTION
- INTERIOR-GLAZED
- INTERIOR ACCESSORY GROOVES

SASH

- .065" TYPICAL WALL THICKNESS
- 1.341" x 1.207" OVERALL PROFILE SIZE
- 7/8" OVERALL INSULATING GLASS CAPABILITY
- TILT/REMOVABLE SASH DESIGNED FOR EASE OF MAINTENANCE
- DOUBLE-WEATHERSTRIPPED STILES
- DOUBLE-WALL GLAZING LEG
- INTEGRAL INTERLOCK
- INTEGRAL LIFT HANDLE AT TOP & BOTTOM RAILS
- WELDED CONSTRUCTION
- EXTERIOR-GLAZED

HARDWARE

- SUITABLE FOR SPIRAL, B & T OR CONSTANT-FORCE BALANCES
- DESIGNED TO ACCEPT A WIDE RANGE OF TILT LATCHES
- WILL ACCOMMODATE MANY CAM LOCK AND KEEPER DESIGNS
- VENTILATION TRAVEL LIMIT DEVICES ARE OPTIONAL

PERFORMANCE

- DP50 ON A 48" x 72" UNIT WITH THE PROPER REINFORCEMENT
- U-VALUE 0.25 (R4) WITH THE APPROPRIATE GLAZING
- FORCED ENTRY RESISTANCE WITH THE REQUIRED LOCK HARDWARE
- ZONE 3 IMPACT RATINGS POSSIBLE